

107540407

Rec'd PCT/PTO 24 JUN 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 July 2004 (22.07.2004)

PCT

(10) International Publication Number
WO 2004/062024 A1

(51) International Patent Classification⁷: H01P 1/201,
1/207

GUGUEN, Charline [FR/FR]; 155F- avenue du Général
Leclerc, F-35700 Rennes (FR).

(21) International Application Number:
PCT/EP2003/051049

(74) Agents: COUR, Pierre et al.; Thomson, 46, quai
Alphonse Le Gallo, F-92100 Boulogne-Billancourt (FR).

(22) International Filing Date:
18 December 2003 (18.12.2003)

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
0300160 6 January 2003 (06.01.2003) FR


(84) Designated States (regional): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): THOM-
SON LICENSING S.A. [FR/FR]; 46, quai Alphonse Le
Gallo, F-92100 Boulogne-Billancourt (FR).

Published:
— with international search report

[Continued on next page]

(54) Title: WAVEGUIDE E-PLANE RF BANDPASS FILTER WITH PSEUDO-ELLIPTIC RESPONSE



WO 2004/062024 A1

(57) **Abstract:** The invention relates to RF bandpass filters with pseudo-elliptic response. In a filter comprising a dielectric substrate 302 placed in E position in a rectangular waveguide 301 and comprising inserts 303-306 on one of the surfaces of the substrate are placed conductors linked electrically to the walls of the guide, and on the other surface of the substrate opposite these conducting inserts are placed electrically floating inserts that make it possible to determine zeros in the transmission curve of the filter. This yields a filter exhibiting a response curve of pseudo-elliptic type which improves the rejection of spurious frequencies without increasing the dimensions of the filter.